Drill Hole and Crack Filler ULTRA

Technical information sheet

750g / Item no. 101476 / EAN 4016215101476



Ideal for quickly repairing, filling and bonding drill holes, cracks and small damaged areas. The fast-curing special levelling compound impresses with its extremely high adhesive strength and versatile range of indoor and outdoor applications. Ready for use after approx. 30 minutes, it adheres reliably to mineral substrates, tiles and other non-absorbent surfaces and ensures long-lasting, clean and professional repair results.

- All-round levelling compound for repairing, filling and bonding
- based on special white cement
- Extremely strong adhesion even on glazed tiles
- Layer thickness 0-10 cm
- Fast curing after 30 minutes
- for indoors and outdoors
- Low chromate according to EU Regulation 1907/2006, Annex XVII (47)

Area of application

Fast-setting cement filler for drill holes and cracks inside/outside, adheres to many substrates, including tiles, also as a repair and bonding compound.

Preparation

The substrate must be dry, sound, clean and free of dust and grease. Pre-treat highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Thoroughly clean and degrease tiles and other non-absorbent substrates.

Processing

Mixing: Sprinkle 750 g of powder into approx. 300 ml of clean, cold water and stir vigorously until a homogeneous mass is formed. If greater stability is required for the application, the amount of water should be reduced to 250 ml. Processing: Process the mixed levelling compound within 30 minutes. The material can be used with a spatula to level out holes/chips up to 10 cm deep in a single layer. Subsequent coats and bonding should only be applied after the material has completely dried. Depending on the application thickness, substrate and ambient temperature, the drying time is approx. 24 hours. Drying time: approx. 5 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); under unfavourable conditions, the drying time is correspondingly longer.

Consumption

per mm application thickness → approx. 1.0 kg/m²

Storage

Keep container tightly closed and store in a cool but frost-free place. Keep out of the reach of children. If unopened and stored properly, shelf life is at least 48 months from date of manufacture (see batch label).

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Observe safety data sheet. Do not apply below +5 °C object and ambient temperature. Clean tools with water immediately after use. Keep packaging tightly closed in a cool, dry place. Only dispose of empty containers for recycling. Hardened material residues can be disposed of with household waste or as construction site waste. Waste code no. EWC 06 02 99. GISCODE ZP1. Low chromate according to EU Regulation 1907/2006, Annex XVII (47). Current safety data sheets are available on our website www.baufan.de

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.