Tile and Surface Filler

Technical information sheet

5kg / Item no. 103647 / EAN 4016215103647



Fine, plastic-reinforced levelling compound for repairing, smoothing and levelling interior wall and ceiling surfaces. Impresses with optimum adhesion even on difficult substrates such as tiles, concrete or plasterboard. Easy to apply, very easy to sand and also suitable for damp rooms. Ideal for preparing smooth, even surfaces for subsequent painting, coating or wallpapering work.

- Very fine, white levelling compound based on special cement
- Ideal for repairing, smoothing, filling and grouting
- Optimum adhesion even on difficult substrates such as painted surfaces and glazed tiles
- Also for damp rooms
- Very good sanding properties
- for indoors
- Low chromate according to EU Regulation 1907/2006, Annex XVII (47)

Area of application

Tile and surface filler for indoors and damp rooms. Adheres to tiles, concrete and plaster, ideal for smoothing, filling and grouting, easy to sand. In the bathroom.

Preparation

The substrate must be dry, sound, clean and free of dust and grease. Remove loose parts, poorly adhering paints and elastic coatings. Pre-treat highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Thoroughly clean and degrease tiles and other non-absorbent substrates.

Processing

Mixing: Sprinkle 2 parts of baufan Tile and Surface Filler into 1 part of clean, cold water and stir until a lump-free mixture is obtained (mixing ratio: 1 kg powder + 500 ml water). The prepared levelling compound remains workable for approx. 40 minutes. Apply baufan tile and surface levelling compound with a spatula or smoothing trowel (layer thickness from 0 to 20 mm). The levelling compound is easy to smooth and felt and can be sanded very well after drying if necessary. After sanding, it is necessary to treat the sanded areas with baufan Deep Primer LF.

Consumption

1 kg powder per 1 m² at 1 mm application thickness

Storage

Keep pack tightly closed in a cool, dry place

Notes

Do not apply below +5 °C object and room temperature. Clean tools with water after use. Take into account the varying absorbency and alkalinity when carrying out repair work. The instructions of the paint and adhesive manufacturers for the pre-treatment of cementitious substrates must be observed. Not suitable for exposure to permanent moisture. Only dispose of empty containers for recycling. Cured material residues can be disposed of with household waste or as construction site waste. Waste code no. EWC 06 02 99.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.