

Lightweight Filler 910

Technical information sheet

/ Item no.034601208 / EAN 4016215105313



This ultra-lightweight filler is ideal for filling joints, cracks and holes, as well as for creating precise joints on interior walls and ceilings. It is particularly easy to apply, remains flexible and ensures clean, even finishes. Once dry, the lightweight filler can be sanded and painted over with ease – perfect for fine touch-ups and detailed work.

- for perfect butt joints
- white
- Application thickness up to 15 mm
- remains slightly flexible even after curing
- can be sanded and painted over
- Can be used indoors and also outdoors with a weather-resistant top coat

Area of application

Ultra-lightweight white filler for living areas, hallways and interior fit-outs: flexibly fills joints, cracks and holes on walls, ceilings, skirting boards and frames indoors!

Preparation

Suitable for all mineral substrates (such as concrete, plaster and masonry) as well as for wood, polystyrene, emulsion paint finishes, varnished surfaces, synthetic resin plasters and similar substrates. The substrate must be clean, dry, sound, and free from dust and grease. Pre-treat highly absorbent, sandy and chalky substrates with profimur Deep Primer LF.

Processing

Before use, cut off at least 1 cm of the nozzle. Apply the lightweight filler to a maximum thickness of 15 mm and smooth it out. Once completely dry (approx. 8 hours, depending on the application thickness and ambient conditions), the lightweight filler can be sanded very easily. For outdoor use, apply a weather-resistant coat shortly after it has dried completely.

Storage

Keep container tightly closed, childproof and store in a cool but frost-free place.

Notes

Do not use at temperatures below +5 °C. Clean tools with water after use.

Only send completely empty containers for recycling. Dried-out material residues can be disposed of as household waste or as construction site waste. Dispose of uncured residues in accordance with EWC code 08 04 10. Do not allow the product to enter the sewerage system, watercourses or the ground.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.