Smoothing and Filling Putty 860

Technical information sheet

/ Item no. 003201208 / EAN 4016215105078
/ Item no. 003207208 / EAN 4016215105108



This levelling and filling compound is ideal for levelling entire surfaces of walls and ceilings, as well as for filling cracks, holes and joints in interior applications. The cellulose-reinforced formula ensures reliable adhesion, easy application and a smooth, seamless finish – perfect for precise results in drywall construction.

- for smoothing the entire surface of ceilings and walls
- for filling cracks and holes, setting dowels and modelling
- for grouting plasterboard and other drywall panels
- with methylcellulose for secure adhesion
- Fire behaviour: A1
- CE-compliant in accordance with DIN EN 13963-3B and DIN EN 13279-1 (gypsum smoothing compound C7/20/2)
- for indoors

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.